



DESCRIPTION: The Inspection Section, made from standard 3/16" track, facilitates inspection and maintenance at points other than the drive unit. It may be placed in any straight run of track. The section is made with the top and sides of the track open down to the center of the chain. This allows for full inspection of the chain for proper lubrication, chain tension and general condition of the conveyor chain. The opening is covered with a removable housing and is equipped with a handle. The Inspection Section also permits easy installation and removal of chain. The most desirable location is at the lowest spot between the output of the drive unit and the take-up. The Inspection Section is finished with R-W standard baked enamel powder coat paint.

APPLICATION: The Inspection Section is used in all "Zig-Zag", "Twin-Trak" and "OverWay" systems. In certain applications, such as a large system, it may be desirable to use several Inspection Sections throughout the system.

SHIPPING WEIGHT: 16.5 lbs.

File Name: 2035-820.dwg

RICHARDS - WILCOX

600 S LAKE ST. AURORA, IL 60506
Phone: (630) 897-6951 Fax: (630) 897-6994
Web Site: www.richardswilcox.com

DESCRIPTION:

INSPECTION SECTION

PART NO.:

2035.00820

REV. LEVEL:

B

DATE:

JUNE 00

NOTICE:

This drawing in design and detail is the property of Richards-Wilcox, any reproductions of this print and/or design without the written consent of Richards-Wilcox is prohibited.

ZZ
33